

UPM Raflatac Graphics Solutions Technical Information

Sales code 303S-P3-HKL-GNE

Product 3.0 mil PVC CLEAR MATTE LAM / P3 / 55# WHITE KRAFT

Face 3.0 mil PVC CLEAR MATTE LAM

Product Self-adhesive monomeric soft-PVC, transparent matte

Use Overlaminating film with UV-absorbers to protect digital large format Inkjet-prints.

Rec. Application Temperature min + 10 °F

Product application temperature - 22 to + 176 °F

Caliper 3.0 mil TAPPI-411

Stretch at break MD >160 % DIN EN ISO 527

Tear resistance MD >26 MPA DIN EN ISO 527

Durability 3 years*

Shelf-life at 73°F/50 % moisturizer 2 years in original packaging

Adhesive P3

Type Permanent

Composition Clear, permanent adhesive

Adhesive strength 14 +/- 6 N/25mm FTM 1 24h on glass

Backing HKL

Product Bleached kraft siliconized paper

Substance weight 55 lbs/ream

Caliper 3.2 mil TAPPI-411

Warranty

UPM Raflatac Graphic Solutions materials are manufactured according to the highest quality standards and pass stringent quality controls prior to dispatch. Any material showing an evident defect of manufacturing will be replaced promptly without charge. The wide range of different applications does not allow to test all possibilities of employment. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For any need of advise or technical support the UPM Raflatac Graphic Solutions technical department will be please to assist.

* Normal storage and handling conditions. For inside applications and short term for outside under middle-European climate conditions unprinted.



WARNING: This product may expose you to Di-isodecyl phthalate (DIDP; CAS RN: 26761-40-0), a substance known to the State of California to cause birth defect or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



UPM

www.upmraflatac.com